



**EURO SECURE**  
SECURING HOMES SINCE 2008



# E3000 INTERCOM

## WIRELESS VIDEO DOOR INTERCOM

STANDARD

ADVANCED

**ELITE**

The ERA E3000's 2.4" LCD screen displays high quality live video and allows you to see and have a two-way conversation with the visitor at your door. The Auto Snapshot feature takes and stores your visitors photo as they press the Intercom Doorbell, giving you a record of who was at your door and when.

**To order visit [www.euro-secure.com](http://www.euro-secure.com) or call 01642 309575**

### Features

- 2.4" TFT LCD video handset display screen
- Video Resolution: 320x240, with 15 frames per second
- Wide angle lens and six LEDs for night vision
- 120° viewing angle
- Auto Snapshot feature takes and stores your visitors photo as they press the Intercom button, stores up to 100 images
- Battery operated weatherproof Outdoor Camera to IP55
- Built-in Microphone and speaker
- Adjustable mic volume and brightness
- Supports up to 2 Outdoor Cameras and 2 Indoor Video Handsets
- Up to 215 metres operating range between Outdoor Camera and Handset
- Power Saving Mode
- Single button door release with door unlock module (sold separately and requires compatible electronic door lock)

**2**  
YEAR  
GUARANTEE

### Ordering Details

| E3000                        | Part Number |
|------------------------------|-------------|
| Wireless Door Video Intercom | E3000       |

| Additional Accessories                  |          |
|---|----------|
| Video Door Intercom Handset and Charger | E3000HSC |
| Video Door Intercom Outdoor Station     | E3000-OS |
| Outdoor Station Power Supply            | CLOSPSU  |

### Technical Information

| Outdoor Camera Station   | Parameter  |
|--------------------------|--|
| Frequency                | 2.4GHz - 2.4835GHz                               |
| Number of Channels       | 120, Duplex Channels                             |
| Data Rate                | 2.0Mbps  |
| Transmitting Power       | 19dBm (TYP)                                      |
| Modulation Type          | GFSK   |
| Transmitting Distance    | Outdoor: 215 metres                              |
| Image Sensor Type        | Colour CMOS Image Sensor                         |
| Image Processing         | H.264  |
| Camera Pixels            | 640x480  |
| White Balance            | Auto   |
| Viewing Angle (Diagonal) | 120°   |
| LED                      | 6 LEDs   |
| Power Requirement        | (+9V-12V) +5% / 2x LR14 (C) 1.5V Batteries       |
| Power Consumption        | 500mA Max (Cells) / 200mA Max (+12V DC)          |
| Operating Condition      | Temperature: -20°C ~ 55°C<br>Humidity: 20% - 90% |
| Dimensions (L x W x H)   | 86 x 160 x 55mm                                  |

| Indoor Video Handset   | Parameter   |
|------------------------|---|
| Frequency              | 2.4GHz - 2.4835GHz                                    |
| Monitor                | 2.4" Colour LCD                                       |
| Data Rate              | 2.0Mbps   |
| Receiving Sensitivity  | 85dBm   |
| Demodulation Type      | GFSK  |
| LCD Resolution         | 320 x 240 (RGB)                                       |
| Transmitting Power     | 19dBm (TYP)   |
| Power Requirement      | BL-5C, 3.7V, 1100mA (Lithium Battery)                 |
| Power Consumption      | 400mA Max   |
| Operating Condition    | Temperature: -10°C ~ 55°C<br>Humidity: 20% - 90%      |
| Dimensions (L x W x H) | Handset: 53 x 188 x 26<br>Charger Base: 80 x 95 x 104 |

### Kit Contents

Outdoor Camera Station (intercom) x 1, Portable Video Handset x 1, Handset Charging Dock x 1, Handset Power Adapter x 1, Installation and Operating Manual, all Fixings and Handset Batteries.